



**WACKER  
NEUSON**  
*all it takes!*

## PSA2 500, 230 V

5000008790

[Home](#) >> [Catalog](#) >> [Products](#) >> [Pumps](#) >> [Trash Pumps](#) >> [Submersible Pumps](#) >> **PSA2 500, 230 V**

### PSA2 500, 230 V

Material number 5000008790

Electric, single phase submersible pump for dewatering, with automatic switch, safety plug, motor protection plug, float and Storz coupling.



### Product details

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Silicon carbide-faced double mechanical seals run in isolated oil filled cavity
- Automatic switch
- Heavy-duty strain relief power cord

### Comes with

- Pump
- Operator's manual

## Technical specifications

### PSA2 500, 230 V

#### MOTOR

Nominal speed	3.000 1/min
---------------	-------------

---

#### MECHANICAL - OUTPUT DETAILS

Solid diameter max.	6,0 mm
Delivery height max.	11,0 m
Flow rate max.	220 l/min

---

#### MECHANICAL DETAILS

Length	220 mm
Width	185 mm
Height	355 mm
Operating weight	10,0 kg
Intake-/Pressure socket-dia.	50 mm

---

#### ELECTRICAL SYSTEM

Cable cross-section	1,0 mm <sup>2</sup>
Length Cable	10,00 m

---

#### ELECTRICAL - OUTPUT DETAILS

Nominal voltage	230 V
Nominal frequency	50 Hz
Starting current full load	2,9 A
Starting current Idle running	7,0 A
Phase	1 ~

**Please Note**

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE