



**WACKER  
NEUSON**  
*all it takes!*

## PS2 800, 230 V

5000620438

[Home](#) >> [Catalog](#) >> [Products](#) >> [Pumps](#) >> [Trash Pumps](#) >> [Submersible Pumps](#) >> **PS2 800, 230 V**



## PS2 800, 230 V

Material number 5000620438

Electric, single phase submersible pump for dewatering, with safety plug, motor protection plug, float and Storz coupling.

### Product details

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Silicon carbide-faced double mechanical seals run in isolated oil filled cavity
- Heavy-duty strain relief power cord

### Comes with

- Pump
- Operator's manual

Technical specifications

PS2 800, 230 V

MOTOR

Nominal speed	2.730 1/min
---------------	-------------

MECHANICAL DETAILS

Length	187 mm
Width	187 mm
Height	341 mm
Operating weight	13,2 kg
Intake-/Pressure socket-dia.	50 mm

ELECTRICAL - OUTPUT DETAILS

Nominal voltage	230 V
Nominal frequency	50 Hz
Starting current full load	5,0 A
Starting current Idle running	12,3 A
Phase	1 ~

ELECTRICAL SYSTEM

Cable cross-section	1,0 mm2
Length Cable	10,00 m

## MECHANICAL - OUTPUT DETAILS

Solid diameter max.	6,0 mm
Delivery height max.	5,0 m
Flow rate max.	310 l/min

### Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE