



**WACKER
NEUSON**
all it takes!

PST3 750, 230 V

5000620454

[Home](#) >> [Catalog](#) >> [Products](#) >> [Pumps](#) >> [Trash Pumps](#) >> [Submersible Pumps](#) >> **PST3 750, 230 V**

PST3 750, 230 V

Material number 5000620454

Electric, single phase submersible trash pump for dewatering, with side discharge, motor protection plug, float and Storz coupling.



Product details

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Silicon carbide-faced double mechanical seals run in isolated oil filled cavity
- Shaft-mounted agitator suspends solids when pumping sand and debris
- Heavy-duty strain relief power cord

Comes with

- Pump
- Operator's manual

Technical specifications

PST3 750, 230 V

MECHANICAL - OUTPUT DETAILS

Solid diameter max.	7,0 mm
Delivery height max.	18,0 m
Flow rate max.	230 l/min

ELECTRICAL SYSTEM

Cable cross-section	1,0 mm ²
Length Cable	10,00 m

ELECTRICAL - OUTPUT DETAILS

Nominal voltage	230 V
Nominal frequency	50 Hz
Starting current full load	4,6 A
Starting current Idle running	14,0 A
Phase	1 ~

MECHANICAL DETAILS

Length	285 mm
Width	184 mm
Height	389 mm
Operating weight	19,0 kg
Intake-/Pressure socket-dia.	80 mm

MOTOR

Nominal speed

2.820 1/min

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE